



### 特点

- 采用1.27mm脚距
- 触片设计特殊,具有优良的抗振动及冲击能力
- 针脚数可分为20,28,32,44,52,68,84.
- 可以进行IR回流或汽相焊接
- 可以通过侧窗检查焊脚

### 电气特性

- 额定电流: 1 A
- 接触电阻: 20 m
- 绝缘电阻: 5000 M
- 耐电压: 600 V r.m.s

### 机械特性

- 适用环境: - 55 ~ + 125

1151 - XXX - 0X - X

塑胶材料及颜色  
( Insulator material and color )  
4 : 棕色(Blown) PPS UL94V-0

镀层代码 (Plating code)

代码 (Code)	定义 (Definition)
1	Gold flash
2	5 μ m Sn Pb

引脚数量 (Pin number)  
020, 028, 032, 044, 052, 068, 084

规格	尺寸	A	B	C	D
20PIN		5.08	15.63	5.08	15.63
28PIN		7.62	18.17	7.62	18.17
32PIN		7.62	18.17	10.16	20.71
44PIN		12.70	23.28	12.70	23.28
52PIN		15.24	25.81	15.24	25.81
68PIN		20.32	30.94	20.32	30.94
84PIN		25.40	36.04	25.40	36.04

### Features

- With 1.27 pitch PCB layout
- Special contact is designed for high reliability and good withstanding to vibration and shock.
- From 20,28,32,44,52,68,to 84 positions are available.
- Applicable for IR-Reflow or vapor phase soldering.
- Visual window for solder-tails inspection.

### Electrical

- Current rating: 1A
- Contact resistance: 20m
- Insulation resistance: 5000 M
- Withstanding voltage: 600V r.m.s

### Mechanical

- Operating temperature: -55 ~ +125

