




Non-shorting





RoHS Compliance



SCHEMATIC



PCB LAYOUT



7	HOOK	S U S	1		8	CASE	NYLON	2	
5	CONTACT	P B S	2	Ag PLATED	6	SPRING	STEEL WIRE	1	
3	TERMINAL	BRASS	6	Ag PLATED	4	COVER	P O M	1	
1	FRAME	NYLON	1		2	KNOB	P O M	1	
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED

SPECIFICATION

TITLE: PUSH SLIDE SWITCH (2P2T)
(LOCKABLE)

RATING: DC 30V 0.1A

MODEL NO: PS-22D07L

CONTACT RESISTANCE: 70mΩ max.

INSULATION RESISTANCE: 100MΩ at 500V DC

TOLERANCE UNIT: MM DWN. *hro*

WITHSTAND VOLTAGE: AC 250V for 1 minute

UP TO 1.0:±0.1 SCALE: 3:1

OPERATION FORCE: REFER ATTACH SPECIFICATION

1.0 TO 10.0:±0.2 VERSION: 01

SWITCHING LIFE: 10K cycles min.

OVER 10.0:±0.3 DRWG NO: APPD. *hro*

