




SCHMATIC



PCB LAYOUT

RoHS
Compliance



7	SPRING	STEEL WIRE	1					
5	CONTACT	P B S	2	Ag PLATED	6	BALL	STEEL	2
3	TERMINAL	BRASS	8	Ag PLATED	4	TERMINAL BASE	PHENOL RESIN	1 NATURAL
1	FRAME	S P C C	1	Ni PLATED	2	KNOB	P O M	1 G 2-15
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY REMARKS

ISSUED

SPECIFICATION

TITLE: SLIDE SWITCH (2P3T)

RATING: DC 30V 0.5A

MODEL NO: SS-23H02 (G)

CONTACT RESISTANCE: 30mΩ max.

INSULATION RESISTANCE: 500MΩ at 500V DC

TOLERANCE

UNIT: MM

DWN.

WITHSTAND VOLTAGE: AC 500V for 1 minute

UP TO 1.0:±0.1

SCALE: 2:1

CHK'D.

OPERATION FORCE: REFER ATTACH SPECIFICATION

1.0 TO 10.0:±0.2

VERSION: 01

APPD.

SWITCHING LIFE: 10K cycles min.

OVER 10.0:±0.3

DRWG NO:

