





SCHEMATIC



PCB LAYOUT



RoHS
Compliance



MODEL NO.	H
TC-00304-00	3.15
TC-00304(A)-00	3.85

NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS
5	CONTACT	S U S	1	Ag PLATED	4	FRAME	NYLON	1	
3	TERMINAL	BRASS	2	Ag PLATED	2	KNOB	NYLON	1	
1	SHELF	S U S	1						

ISSUED

SPECIFICATION

TITLE: TACT SWITCH



RATING: DC 12V 50mA
 CONTACT RESISTANCE: 100mΩ Max.
 INSULATION RESISTANCE: 100MΩ at 500V DC
 WITHSTAND VOLTAGE: AC 250V for 1 minute.
 OPERATION FORCE: REFER ATTACH SPECIFICATION
 SWITCHING LIFE: 50k Cycles Min.

MODEL NO: TC-00304 ()-00

TOLERANCE	UNIT: MM	DWN.	<i>hws</i>
UP TO 1.0:±0.1	SCALE: 4:1	CHK'D.	<i>hws</i>
1.0 TO 10.0:±0.2	VERSION: 01	APPD.	<i>hws</i>
OVER 10.0:±0.3	DRWG NO:		