



特点

此类双凸圆形排针是专为板间连接而设计的
 引脚端有折弯
 引脚间距: 标准 2.54mm
 可以按照客户要求裁成任意脚数

电气特性

额定电流: 1 A
 接触电阻: 10 m
 绝缘电阻: 1000 M
 耐电压: 1000 V.r.m.s.

机械特性

保持力: 20 N/pin
 适用环境: - 55 ~ + 125

Features

These profile type, Straight terminal adapter strip are designed for PC board "Sandwich Applications". The contacts have be kinked.
 Pitch: standard 2.54mm
 Contacts can be ordered upon customer's request.

Electrical

Current rating: 1A
 Contact resistance: 10m
 Insulation resistance: 1000 M
 Withstanding voltage: 1000V r.m.s

Mechanical

Extraction force: 20 N/pin
 Operating temperature: -55 ~ +125

1128 - XX1 - XX - 1

塑胶材料及颜色
 (Insulator material and color)
 1:黑色(Black),PBT+30%GF,UL94V-0

镀层代码 (Plating coat)

代码 (Code)	定义 (Definition)
10	0.25 μm Au
90	5 μm Sn Pb

排数(Number of rows)

代码 (Code)	定义 (Definition)
1	单排(Single row)

引脚数量 (Pin number)

代码 (Code)	定义 (Definition)
1 ~ 32	单排(Single row)

1128系列,折弯形式
 (1128 Series with kink)

