



MATERIALS AND FINISH

SHELL : STEEL MATERIAL, NICKEL FINISHED
DIMPLES ON PLUG ONLY

INSULATOR : PBT THERMOPLASTIC, 30% GLASS
FILLED, UL 94V-0 RATED, BLACK COLOR

CONTACT MATERIAL: BRASS

CONTACT FINISH : SELECTIVE GOLD FLASHED

GROUNDING BRACKET : BRASS MATERIAL, TIN FINISHED

RIVETED INSERT : BRASS MATERIAL , NICKEL FINISHED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS

CONTACT RESISTANCE : 30 MILLIOHMS MAX.

DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.

INSULATION RESISTANCE : 5000 MEGAOHMS MIN.

TEMPERATURE RATING : -55°C ~ +105°C

Drawn by	jankey	2007.11.14
Designed by	jankey	2007.11.14
Approved by	jankey	2007.11.14
	Sheet 1 of 1	Code 000
Dimensions in mm(inches)		Scale 1:1
Tolerances on:XX+/-0.13		Angles+/-2°

HDB 15母 180°

Ver A0 Part No: 1157A -015-201-00