

# 4X18 IDC线缆连接器 1811 系列

4 x 18 IDC cable connector 1811 Series



## 特点

- 4排18列的线缆连接器
- 2mm网格间距
- 带有金属屏蔽外壳
- 适用于从拉手条前端出线
- 源自 IEC61076-4-104 标准

## 电气特性

- 额定电流: 1.5A at 20 , 1 A at 70
- 接触电阻: 20 m
- 绝缘电阻: 10000 M
- 耐电压: 1000 V.r.m.s.

## 机械特性

- 插入力: 0.75 N/pin
- 拔出力: 0.15 N/pin
- 适用环境: - 55 ~ +125

## Features

- 4 rows with 72 contacts
- Grid at 2mm spacing
- Be shielded by metal cover
- Be applicable to fetch out cable from the front of Slot
- Be derived from IEC 61076-4-104

## Electrical

- Current rating: 1.5A at 20 , 1A at 70
- Contact resistance: 20m
- Insulation resistance: 10000 M
- Dielectric withstand voltage: 1000V.r.m.s.

## Mechanical

- Insertion force: 0.75N/pin
- Extraction force: 0.15N/pin
- Operating temperature: -55 ~ +125

1811 - 418 - XX - X

安装螺钉螺纹规格(Set screw thread standard)

- M3
- #4 - 40UNC
- X. 客户指定(Customer specifies)

电镀等级(Grade of the plating)

代码 (code)	触点镀层 (Contacts plating)
2	GLASS I
3	GLASS II
4	GLASS III
5	High Grade Telecom Class

线规号(Wire gauge)

代码 (code)	线规号 (Wire gauge)
1	AWG24/26
2	AWG28/30

孔位分布为4排18列(The bore distributes of Bac to 4 rows x 18 lines)

屏蔽/后出线  
(Shielding/rear outlet)

IDC系列代码 (IDC Series code)

